Art Unit No.: 2686

Amendments to the Claims

- 1. (Currently Amended) A software defined radio comprising:
- a plurality of communication schemes;

a configuration system for selectively enabling one of the plurality of communication schemes comprising a processor, a smartcard reader and a memory;

wherein a one of the plurality of communication schemes is selected and enabled by the processor based on information from a user's smartcard, and wherein said information includes at least a security authorization.

- 2. (Original) The software defined radio according to claim 1, wherein the plurality of communication schemes includes a plurality of communication protocols.
- 3. (Original) The software defined radio according to claim 1, wherein the plurality of communication schemes include a plurality of modulation/demodulation techniques.
- 4. (Original) The software defined radio according to claim 1, wherein the plurality of communication schemes include a plurality of coding/decoding techniques.
- 5. (Original) The software defined radio according to claim 1, wherein the information retrieved from the smart card comprises a communication scheme.
 - 6. (Cancelled).
- 7. (Original) The software defined radio according to claim 1, comprising a programmable A/D converter or a programmable D/A converter.

Application Serial No. 10/661,487 Art Unit No.: 2617

8. (Original) The software defined radio according to claim 1, comprising a programmable digital signal processor.

- 9. (Previously Presented) The software defined radio according to claim 7, wherein a program for driving the programmable A/D converter or programmable D/A converter is stored in the memory.
- 10. (Previously Presented) The software defined radio according to claim 8, wherein a program for driving the programmable digital signal processor is stored in the memory.
- 11. (Currently Amended) In a software defined radio ("SDR"), the SDR comprising layered communication information and plural communication protocols, a method of configuring the SDR, the improvement comprising the steps of:

providing a smartcard containing configuration information; retrieving the configuration information from the smartcard; and, configuring the SDR based on the configuration information, wherein said information includes at least a security authorization.

- 12. (Previously Presented) The method of claim 11, further comprising the step of selecting the layered communication information and plural communication protocols is based on the configuration information.
 - 13. (Cancelled).

Application Serial No. 10/661,487 Art Unit No.: 2617

- 14. (Previously Presented) The method of claim 11, wherein the step of configuring further comprises selecting and executing stored software modules for driving generic radio hardware according to the configuration information.
- 15. (Previously Presented) The method of claim 14, wherein the generic radio hardware is selected from the group consisting of microprocessors, modulators/demodulators, and digital signal processors.
- 16. (Currently Amended) In a software defined radio ("SDR") comprising multiple link-layered communication protocols, a method for configuring the SDR, the improvement comprising retrieving configuration instructions from a smartcard containing a specific configuration, wherein said configuration instructions includes at least a security authorization.
- 17. (Original) The method of claim 16, wherein the specific configuration includes, modulation/demodulation type, digital processing and operational protocols.
- 18. (Previously Presented) The method of claim 16, wherein the specific configuration is selected from the group consisting of AMSSB, FM, PSK, QPSK, QAM, FSK, TDMA, CDMA, FDMA, AMPS, and GSM.

Art Unit No.: 2617

- 19. (Original) A software defined radio comprising a RF Section, a IF section and a baseband section, wherein the IF section and the baseband sections are programmable, a plurality of software modules containing programs for the IF section and the baseband section, the improvement comprising a smart card reader, wherein information retrieved by the smart card reader designates the respective programs for the IF section and the baseband section.
- 20. (Previously Presented) The software defined radio of claim 19, wherein the information is based on service requirements of a user.
- 21. (Previously Presented) The software defined radio of claim 19, wherein the information is based on mission requirements of a user.
- 22. (Previously Presented) The software defined radio of claim 19, wherein the information is based on security status of the user.
- 23. (Original) The software defined radio of claim 19, wherein programs are selected from the group enabling AMSSB, FM, PSK, QPSK, QAM, FSK, TDMA, CDMA, FDMA, AMPS, and GSM configurations.

RF-216

Application Serial No. 10/661,487

Art Unit No.: 2617

Response to Office Action December 5, 2006

24. (Currently Amended) A method for configuring a radio with software for communicating in a wireless environment, the method comprising the steps of: receiving configuration information from a smart card in communication with the radio; configuring the radio in accordance with the configuration information and verifying current validity of the Smartcard, said configuration information allowing the radio to communicate in the wireless environment, wherein said configuration information includes at least a verification authorization.

25. (Original) The method of Claim 24, further comprising the step of verifying current validity of the smartcard.